

## TECHNICAL DATA SHEET

### MANHATTAN MANHATTAN MONOBLOC SINK MIXER

#### Product Specification

<b>Product Code:</b>	MH SNK C (As shown) MH SNK WHT MH SNK MOC MH SNK BGE
<b>Finishes:</b>	Chrome, White, Mocca, Beige
<b>Product Type:</b>	Contemporary
<b>Construction:</b>	Bodies are of all brass construction and are designed to conform to BS EN 200
<b>Cartridge/Valve Type:</b>	Ceramic disc valves
<b>Supply:</b>	Suitable for all plumbing systems
<b>Inlet Connections:</b>	15mm copper tail pipes
<b>Water Pressure:</b>	Min. 0.2 bar, Max. 8.0 bar



#### Additional Information

- Dual flow
- Chrome plated to BS EN 248
- Supplied with 15mm copper tail pipes
- Compatible with the following flow limiters: ECO TAP1  
ECO TAP2  
ECO TAP3  
ECO TAP4  
ECO TAP5  
ECO TAP6
- Flow limiters have to be fitted into a 15mm compression fitting

**Technical Advice:** For further information please call 0844 7016273 or email [customer@bristan.com](mailto:customer@bristan.com).  
**Guarantee:** 5 years covering manufacturing faults.

#### Compliance/Approvals

**WRAS:** Manufactured to comply with WRAS

#### Flow Rates (litres per min.)

System Pressure	0.2bar	0.5bar	1bar	2bar	3bar	5bar
MH SNK	4.1	7.2	10.4	14.9	18.6	24.1

