

MIRA GEM 88

Part Number: EV, Chrome: 1.1557.001
 Part Number: BIV, Chrome: 1.1557.003
 Part Number: BIR, Chrome: 1.1557.005



CERAMIC FLOW CONTROL – RESISTS LIMESCALE

TEMPERATURE CONTROL

Manual temperature control

EASY TO FIT

Quickly and easily fits onto reversed inlet supplies.
 EV has adjustable inlets (149-154 mm)

EASY TO SERVICE

Replaceable cartridge

FOR YOUR CUSTOMER

Separate flow and temperature controls

Ceramic flow control – resists limescale

3 spray 9 cm showerhead with rub clean nozzles



MIRA GEM 88 EV

MIRA GEM 88 BIR

MIRA GEM 88 BIV

TECH DETAILS

TEMPERATURE CONTROL

Control type: Manual

INSTALLATION

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression (EV); ½" BSP Female (BIV & BIR)

Outlet connections: ½" BSP Male flat face (EV); ½" BSP Female (BIV & BIR)

Reversed inlets supported: Yes

SUPPLY CONDITIONS (hot and cold supplies to be at nominally equal pressure)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating); 55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

PERFORMANCE

Flow rate (at handset): 13 l/min at 0.5 bar

ACCESSORIES

Wide range of accessories available at www.mirashowers-store.co.uk

TECH DRAWINGS

