

MIRA ADVANCE ATL FLEX LOW PRESSURE

Part Number: 9.0kW White/Chrome: 1.1759.003



TAKES THE PRESSURE
OUT OF INSTALLING
AT LOW PRESSURES



TEMPERATURE CONTROL

Thermostatic temperature stability

EASY TO FIT

Retrofits Triton, Aqualisa and many other electric showers

EASY TO SERVICE

Easy Filter access

FOR YOUR CUSTOMER

Separate flow and temperature controls

Push button start/stop

IMPORTANT:

THIS IS A PUMPED ELECTRIC SHOWER FOR INSTALLATION ONTO GRAVITY FED COLD WATER CISTERNS. IT IS NOT SUITABLE FOR INSTALLATION DIRECTLY ONTO COLD MAIN SUPPLIES

TECH DETAILS

TEMPERATURE CONTROL

Control type: Thermostatic (Electronic)

INSTALLATION

Power options: 9.0kW 240V AC (8.2kW 230V AC) • 9.8kW 240V AC (9.0kW 230V AC)

Supply voltage: 230v ± 10%

Supply rating: 40 amp (9.0kW); 45 amp (9.8kW)

Terminal block connections: Maximum 16 mm²

Water entry points: Right – rising, falling or rear

Inlet connections: Brass Inlet Connector. ½" BSP Male and 15 mm compression fitting

Outlet connections: ½" BSP Male

SUPPLY CONDITIONS (hot and cold supplies to be at nominally equal pressure)

Minimum maintained pressure: 0.008 bar (80 mm head)

Maximum maintained pressure: 1.0 bar (10 metre head)

Maximum static pressure: 1.0 bar (10 metre head)

PERFORMANCE

Temperature stability: ± 1°C

SAFETY FEATURES

Phased shutdown: Yes

Factory set to safe max temp: Adjustable to 8 different max temp settings (37°C - 48°C)

Sensi-flo™: Yes

ACCESSORIES

Wide range of accessories available at www.mirashowers-store.co.uk

TECH DRAWINGS

